


## Heat Shrink Tube, Dual Wall, $\phi$ 7.9mm, Black, PE

- High resistance to impact and abrasion
- Adhesive lined
- Shrink ratio: 3:1
- Continuous operating temperature: -45°C to 125°C
- Shrink temperature: 120°C min



### Product Classification

Item Number	6009339
Part Number	-
Detail Description	Heat shrink tube, dual Wall, $\phi$ 7.9mm, Black, PE

### General Specifications

Material	PE
Color	Black
Cable Range	$\Phi$ 2.7 - 7.9 mm   0.106 - 0.311 in
Adhesive(Y/N)	Y
Shrink Ratio	3:1

### Dimensions

Expanded Inside Diameter, minimum	7.9 mm   0.311 in
Recovered Inside Diameter, maximum	2.7 mm   0.106 in
Total Recovered Wall Thickness	1.35 mm   0.053 in

### Environmental Specifications

Operating Temperature	-45 °C to +125 °C (-49 °F to +257 °F)
Shrink Temperature Minimum	120 °C (248 °F)

### Electrical Specifications

Voltage	600 V
Dielectric Strength	$\geq$ 15 KV/mm

### Packaging and Weights

Roll Diameter	500 mm   1.64 in
Roll Height	34 mm   0.11 in
Meter per roll	100 m
UOM	1 Pcs

Packaging	Bag
Weight, Gross	0.752 kg   1.658 lbs
<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

