

## Heat Shrink Tube, Dual Wall, $\phi$ 25.4mm, Black, PE

- High resistance to impact and abrasion
- Adhesive lined
- Shrink ratio: 3:1
- Continuous operating temperature: -45°C to 125°C
- Shrink temperature: 120°C min



### Product Classification

Item Number	6009341
Part Number	-
Detail Description	Heat shrink tube, dual Wall, $\phi$ 25.4mm, Black, PE

### General Specifications

Material	PE
Color	Black
Cable Range	$\phi$ 8.5 - 24.0 mm   0.34 - 0.94 in
Adhesive(Y/N)	Y
Shrink Ratio	3:1

### Dimensions

Expanded Inside Diameter, minimum	25.4 mm   1.0 in
Recovered Inside Diameter, maximum	8.5 mm   0.34 in
Total Recovered Wall Thickness	2.0 mm   0.078 in

### Environmental Specifications

Operating Temperature	-45 °C to +125 °C (-49 °F to +257 °F)
Shrink Temperature Minimum	120 °C (248 °F)

### Electrical Specifications

Voltage	600 V
Dielectric Strength	$\geq$ 15 KV/mm

### Packaging and Weights

Roll Diameter	500 mm   1.64 in
Roll Height	34 mm   0.11 in
Meter per roll	25 m
UOM	1 Pcs

---

Packaging	Bag
-----------	-----

---

Weight, Gross	2.42 kg   5.33 lbs
---------------	--------------------

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

---

RoHS	Compliant
------	-----------

---

UL	Compliant
----	-----------

---

