

Cold Shrink Termination, Up to 35KV, For 50-150mm² Cable

- Easy installation on a wide range of cable sizes
- No heat or flame is needed during installation
- Suitable for 26 to 35KV outdoor industrial applications
- Operation Temperature -40°C~90 °C



Product Classification

Item Number	TBD 29
Part Number	-
Detail Description	Cold Shrink termination, up to 35KV, for 50-150mm ² Cable

General Specifications

Material	Silicone
Color	Black
Core Type	Single
Number Of Skirts	9
Rated Voltage	26/35 KV
Voltage Application	Medium Voltage

Dimensions

Length	460.0 mm 18.11 in
Skirts Width	120.0 mm 4.72 in
Cross Section	50-150 mm ²
Compatible Cable Insulation OD, maximum	42.5 mm 1.67 in
Compatible Cable Insulation OD, minimum	31.0 mm 1.22 in

Electrical Specifications

AC Voltage Withstand, 5 min	117 KV, No flash
DC Voltage Withstand, 15 min	104 KV, No flash

Environmental Specifications

Operating Temperature	-40 °C to +90 °C (-40 °F to +194 °F)
UV Resistance	≥720 hours, base on ISO4892.3-1994
Flame Retardant	UL94 V0

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 11, 2025

Public

Height, Packed	300 mm 11.81 in
Width, Packed	450 mm 17.72 in
UOM	Pcs
Packaging	Bag
Weight, Gross	1.05 kg 0.235 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

