

Heat Shrink Tube, Dual Wall, $\phi 9.5\text{mm} \times 1.22\text{m}$, Clear, EVA

- **Covering and protecting bare splices or cable connections**
- **Various range of application**
- **UL certificated**



Product Classification

Item Number	6008678
Part Number	-
Detail Description	Heat shrink tube, dual wall, $\phi 9.5\text{mm} \times 1.22\text{m}$, Clear

General Specifications

Material	EVA
Color	Clear
Shrink Ratio	$\geq 3:1$
Applied Cable Range	3.2 - 9.5 mm 0.126 - 0.374 in

Dimensions

Inner diameter Before Shrink, Minimum	9.5 mm 0.374 in
Inner diameter After Shrink, Maximum	3.2 mm 0.126 in
Thickness After Shrink	1.4 mm 0.055 in
Length	1.22 m 48.0 in

Environmental Specifications

Continuous Operating Temperature	-55 °C to +125 °C (-67 °F to +257 °F)
Tensile Strength	≥ 10.4 Mpa, base on GB/T1408
Longitudinal Change	$\leq 5\%$
Dielectric Strength	≥ 15 KV/mm, base on GB/T1408

Packaging and Weights

Height, Packed	185 mm 7.28 in
Width, Packed	1400 mm 55.12 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.045 kg 0.099 lbs

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
 Revised: Nov 24, 2025
 Public

Page 1 of 2

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant