

Copper Lug, 10mm², one hole M8, Hook Type, without inspection window


- **Copper cable lugs are designed for connecting copper cables, coils and Bus-bars**
- **Easy to Install**
- **The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.**
- **The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.**

**Product Classification**

Item Number	6009656
Part Number	-
Detail Description	Copper Lug, 10mm ² , one hole M8, Hook Type, without inspection window

General Specifications

Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	Without inspection window

Dimensions

Bolt Size (E)	0.34 in 8.6 mm
Tang Width (C)	0.61 in 15.5 mm
Barrel length (B)	0.35 in 20.8 mm
Overall length (L)	2.24 in 57.0 mm
Inner diameter (d)	0.17 in 4.4 mm
Outer diameter (D)	0.28 in 7.0 mm

Electrical Specifications

Rating - Maximum Voltage	35KV
--------------------------	------

Environmental Specifications

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
 Revised: Aug 30, 2024
 Public

Page 1 of 2

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included Lug

Packaging Quantity and UOM 1 pcs

Piece Weight 0.02 lb | 0.008 kg

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant