

Hook Cable Clamp, M Type, 3 holes, 2x4.5-6mm+1x12-22mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round ø 8-25 and flat 3-25 mm



| Product Classification | |
|-----------------------------------|--|
| Item Number | 6003326 |
| Part Number | - |
| Detail Description | Hook cable clamp, for 2x4.5-6mm OD cable and 1x12-22mm OD cable, hooking on round ø8-25 and flat 3-25 mm |
| General Specifications | |
| Metal Material | Stainless Steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 3 |
| Dimensions | |
| Height | 145.0 mm 5.71 in |
| Width | 41.5 mm 1.63 in |
| Length | 33.0 mm 1.30 in |
| Compatible Cable 1 OD, maximum | 6.0 mm 0.236 in |
| Compatible Cable 1 OD, minimum | 4.5 mm 0.177 in |
| Compatible Cable 2 OD, maximum | 22.0 mm 0.86 in |
| Compatible Cable 2 OD, minimum | 12.0 mm 0.47 in |
| Environmental Specifications | |
| Operating Temperature | -40°C to +85°C(-40°F to+185°F) |
| Environmental Strength Capability | Double Cable Weight |
| UV Resistance | ≥720 Hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 Hours,base on IEC 60068-2-6-2007 |
| Packaging and Weights | |
| Height, Packed | 320 mm 12.60 in |
| Width, Packed | 220 mm 8.66 in |



| | |
|--------------------------------------|--|
| UOM | 1 Pcs |
| Packaging | Bag |
| Weight, Gross | 0.098 kg 0.216 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

