MAXDAO

Rotary Waveguide Cable Clamp, Rubber Lining Hole 38x22mm, For R84 Waveguide

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Universal fixing design on pole**
- **Operation Temperature -40~85 ℃**

Classification

Item Number	6003643
Part number	-
Detail Description	Rotary waveguide cable clamp, for R84 rectangular waveguide

General Specifications

Metal Material	Stainless Steel 304
Metal Color	Natural
Rubber Material	Natural Rubber
Rubber Color	Black
Fit Mounting Pole OD	40-150 mm | 1.57- 5.91 in
Waveguide Size	WR112 | R84

Dimensions

Threaded Rod Length	400.0 mm | 15.75 in
Rubber Lining Hole	38.0x22.0 mm | 1.50x0.87 in

Environmental Specifications

Operating Temperature	-40°C to +85°C(-40°F to+185°F)
UV Resistance	≥720 Hours, base on ISO4892.3-1994
Salt Spray	≥720 Hours, base on IEC60028-2-11

Packaging and Weights

Height, Packed	600 mm | 23.62 in
Width, Packed	200 mm | 7.87 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.412 kg | 0.908 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this

quality management system	
RoHS	Compliant