


Feeder Cable Clamp, 4 holes, 2x4.5-7mm+2x10-15mm, Q235 Plated Dacromet

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



Classification	
Item Number	6004559
Part number	-
Detail Description	Feeder cable clamp, for 2x4.5-7mm OD cable and 2x10-15mm OD cable, Q235 plated dacromet
General Specifications	
Metal Material	Steel Q235
Surface Treatment	Plated Dacromet
Block Material	PP
Block Color	Black
Rubber Material	EPDM
Rubber Color	Black
Mounting	M6 Hardware
Cables Per Hanger	4
Dimensions	
Height	36.0 mm 1.42 in
Width	40.0 mm 1.57 in
Length	160.0 mm 6.30 in
Threaded Rod Length	90.0 mm 3.54 in
Compatible Cable 1 OD, maximum	7.0 mm 0.276 in
Compatible Cable 1 OD, minimum	4.5 mm 0.177 in
Compatible Cable 2 OD, maximum	15.0 mm 0.59 in
Compatible Cable 2 OD, minimum	10.0 mm 0.39 in
Environmental Specifications	
Operating Temperature	-40°C to +85°C(-40°F to+185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994



Packaging and Weights	
Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.205 kg 0.452 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

