**MAXDAO**

# Hook Cable Clamp, M Type, 12 holes, 12x1/2"S

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Operation Temperature -40~85 ℃**
- **Hooking on round ø 8-25 and flat 3-25 mm**

## Product Classification

| | |
|---|---|
| Item Number | 6004871 |
| Part Number | - |
| Detail Description | Hook cable clamp, for 12x1/2" superflex cable, hooking on round ø8-25 and flat 3-25 mm |

## General Specifications

| | |
|---|---|
| Metal Material | Stainless Steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 12 |

## Dimensions

| | |
|---|---|
| Height | 220.0 mm \| 8.66 in |
| Width | 45.0 mm \| 1.77 in |
| Length | 56.7 mm \| 2.23 in |
| Compatible Cable Jacket OD, maximum | 14.0 mm \| 0.55 in |
| Compatible Cable Jacket OD, minimum | 13.0 mm \| 0.51 in |

## Environmental Specifications

| | |
|---|---|
| Operating Temperature | -40°C to +85°C(-40°F to+185°F) |
| Environmental Strength Capability | Double Cable Weight |
| UV Resistance | ≥720 Hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 Hours,base on IEC 60068-2-6-2007 |

## Packaging and Weights

| | |
|---|---|
| Height, Packed | 300 mm \| 11.81 in |
| Width, Packed | 120 mm \| 4.72 in |
| UOM | 1 Pcs |

**For more information, please visit:**
www.maxdao.com

| Packaging | Bag |
| --- | --- |
| Weight, Gross | 0.258 kg | 0.569 lbs |

## Certifications and Compliance

| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| --- | --- |
| RoHS | Compliant |

TEMPLATE# ITM0401   VERSION A/8   DATE 08/20/2024

**For more information, please visit:**
www.maxdao.com