

Feeder Cable Clamp, 6 holes, 3x4-8mm+3x15-22mm, Q235 Plated Dacromet

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



Classification	
Item Number	6005366
Part number	-
Detail Description	Feeder cable clamp, for 3x4-8mm OD cable and 3x15-22mm OD cable, Q235 plated dacromet
General Specifications	
Metal Material	Steel Q235
Surface Treatment	Plated Dacromet
Block Material	PP
Block Color	Black
Rubber Material	EPDM
Rubber Color	Black
Mounting	M8 Hardware
Cables Per Hanger	6
Dimensions	
Height	36.0 mm 1.42 in
Width	60.0 mm 2.36 in
Length	230.0 mm 9.06 in
Threaded Rod Length	160.0 mm 6.30 in
Compatible Cable 1 OD, maximum	8.0 mm 0.315 in
Compatible Cable 1 OD, minimum	4.0 mm 0.157 in
Compatible Cable 2 OD, maximum	22.0 mm 0.86 in
Compatible Cable 2 OD, minimum	15.0 mm 0.59 in
Environmental Specifications	
Operating Temperature	-40°C to +85°C(-40°F to+185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994



Packaging and Weights	
Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.295 kg 0.650 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

