


Feeder Cable Clamp, 6 holes, 2x11-23mm+2x4-7mm

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Operation Temperature -40~85 °C**

**Classification**

| | |
|--------------------|---|
| Item Number | 6006099 |
| Part number | - |
| Detail Description | Feeder cable clamp, for 2x11-23mm OD cable and 2x4-7mm OD cable |

General Specifications

| | |
|-------------------|---------------------|
| Metal Material | Stainless Steel 304 |
| Metal Color | Natural |
| Block Material | PP |
| Block Color | Black |
| Rubber Material | EPDM |
| Rubber Color | Black |
| Mounting | M8 Hardware |
| Cables Per Hanger | 4 |

Dimensions

| | |
|--------------------------------|--------------------|
| Height | 40.0 mm 1.57 in |
| Width | 85.5 mm 3.36 in |
| Length | 190.0 mm 7.48 in |
| Threaded Rod Length | 120.0 mm 4.72 in |
| Compatible Cable 1 OD, maximum | 23.0 mm 0.91 in |
| Compatible Cable 1 OD, minimum | 11.0 mm 0.43 in |
| Compatible Cable 2 OD, maximum | 7.0 mm 0.276 in |
| Compatible Cable 2 OD, minimum | 4.0 mm 0.157 in |

Environmental Specifications

| | |
|-----------------------------------|------------------------------------|
| Operating Temperature | -40°C to +85°C(-40°F to+185°F) |
| Environmental Strength Capability | Double Cable Weight |
| UV Resistance | ≥720 Hours, base on ISO4892.3-1994 |

Packaging and Weights

| | |
|----------------|----------------------|
| Height, Packed | 300 mm 11.81 in |
| Width, Packed | 300 mm 11.81 in |
| UOM | 1 Pcs |
| Packaging | Bag |
| Weight, Gross | 0.275 kg 0.606 lbs |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |