

## Hook Cable Clamp, E Type, 8 holes, 4x12-22mm+4x4.5-7mm

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Operation Temperature -40~85 °C**
- **Hooking on section 40x22mm, round ø3-12mm and flat 3-12mm**



### Product Classification

|                    |  |
|--------------------|--|
| Item Number        | 6009472  |
| Part Number        | -  |
| Detail Description | Hook cable clamp, for 4x12-22mm OD cable and 4x4.5-7mm OD cable, hooking on section 40x22mm, round ø3-12mm and flat 3-12mm |

### General Specifications

|                   |                     |
|-------------------|---------------------|
| Metal Material    | Stainless Steel 304 |
| Block Material    | PA6                 |
| Block Color       | Black               |
| Cables Per Hanger | 8                   |

### Dimensions

|                                |                     |
|--------------------------------|---------------------|
| Height                         | 310.0 mm   12.20 in |
| Width                          | 41.5 mm   1.63 in   |
| Length                         | 33.0 mm   1.30 in   |
| Compatible Cable 1 OD, maximum | 22.0 mm   0.86 in   |
| Compatible Cable 1 OD, minimum | 12.0 mm   0.47 in   |
| Compatible Cable 2 OD, maximum | 7.0 mm   0.277 in   |
| Compatible Cable 2 OD, minimum | 4.5 mm   0.177 in   |

### Environmental Specifications

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Operating Temperature             | -40°C to +85°C(-40°F to+185°F)      |
| Environmental Strength Capability | Double Cable Weight                 |
| UV Resistance                     | ≥720 Hours, base on ISO4892.3-1994  |
| Vibration Test                    | ≥6 Hours,base on IEC 60068-2-6-2007 |

### Packaging and Weights

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
 Revised: Sep 19, 2024  
 Public

Page 1 of 2

|                |                      |
|----------------|----------------------|
| Height, Packed | 300 mm   11.81 in    |
| Width, Packed  | 120 mm   4.72 in     |
| UOM            | 1 Pcs                |
| Packaging      | Bag                  |
| Weight, Gross  | 0.246 kg   0.542 lbs |

**Certifications and Compliance**

|               |  |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS          | Compliant  |