

Whipsock, Double Eye,Hose OD 1.575-1.969 in Galvanized Steel

- **High-pressure hose safety restraint device, reliably stops the unpredictable and potentially hazardous movement of a high-pressure hose.**
- **Suited for applications where the media being transferred is under higher working pressures such as air, water, hydraulic, and slurry**
- **Prevent injuries or accidents resulting from hose or coupling failure.**
- **Two mounting points and the long gripping area**
- **CE certified**



Product Classification

Item Number	6006691
Part Number	-
Detail Description	Whipsock, Double Eye,Hose OD 1.575-1.969 in Galvanized Steel

Details

Cable Range	1.575-1.969 in 40-50 mm
Mesh Length	31.8 in 800.0 mm
Eye Length	7.1 in 180.0 mm
Max. Working Pressure	1000 psi
Working Load	2425 lbs 1100 kg (Safety Factor 5*)
Approximate Break Strength	12125 lbs 5500 kg
Mesh Material	Galvanized Steel

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	1.77 lb 0.80 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant