

**Feeder Cable Clamp, 4 holes, 2x4.5-7mm+2x22-29mm, Q235 Plated Dacromet**

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Operation Temperature -40~85 °C**

**Classification**

Item Number	6004421
Part number	-
Detail Description	Feeder cable clamp, for 2x4.5-7mm OD cable and 2x22-29mm OD cable, Q235 plated dacromet

**General Specifications**

Metal Material	Steel Q235
Surface Treatment	Plated Dacromet
Block Material	PP
Block Color	Black
Rubber Material	EPDM
Rubber Color	Black
Mounting	M8 Hardware
Cables Per Hanger	4

**Dimensions**

Height	36.0 mm   1.42 in
Width	68.0 mm   2.68 in
Length	210.0 mm   8.27 in
Threaded Rod Length	140.0 mm   5.51 in
Compatible Cable 1 OD, maximum	7.0 mm   0.276 in
Compatible Cable 1 OD, minimum	4.5 mm   0.177 in
Compatible Cable 2 OD, maximum	29.0 mm   1.14 in
Compatible Cable 2 OD, minimum	22.0 mm   0.86 in

**Environmental Specifications**

Operating Temperature	-40°C to +85°C(-40°F to +185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994

**Packaging and Weights**

Height, Packed	320 mm   12.60 in
Width, Packed	220 mm   8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.245 kg   0.540 lbs

**Certifications and Compliance**

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant