


Feeder Cable Clamp, 2 holes, 2x1/2"

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



|                                   |                                              |
|-----------------------------------|----------------------------------------------|
| Classification                    |                                              |
| Item Number                       | 6006635                                      |
| Part number                       | -                                            |
| Detail Description                | Feeder cable clamp, for 6x1/2" coaxial cable |
| General Specifications            |                                              |
| Metal Material                    | Stainless Steel 304                          |
| Metal Color                       | Natural                                      |
| Block Material                    | PP                                           |
| Block Color                       | Black                                        |
| Mounting                          | M6 Hardware                                  |
| Cables Per Hanger                 | 2                                            |
| Dimensions                        |                                              |
| Height                            | 36.5 mm   1.44 in                            |
| Width                             | 58.8 mm   2.31 in                            |
| Length                            | 90.0 mm   3.54 in                            |
| Threaded Rod Length               | 60.0 mm   2.36 in                            |
| Compatible Cable OD, maximum      | 17.0 mm   0.67 in                            |
| Compatible Cable OD, minimum      | 16.0 mm   0.63 in                            |
| Environmental Specifications      |                                              |
| Operating Temperature             | -40°C to +85°C(-40°F to+185°F)               |
| Environmental Strength Capability | Double Cable Weight                          |
| UV Resistance                     | ≥720 Hours, base on ISO4892.3-1994           |
| Packaging and Weights             |                                              |
| Height, Packed                    | 320 mm   12.60 in                            |
| Width, Packed                     | 220 mm   8.66 in                             |
| UOM                               | 1 Pcs                                        |



|                                      |                                                                                |
|--------------------------------------|--------------------------------------------------------------------------------|
| Packaging                            | Bag                                                                            |
| Weight, Gross                        | 0.179 kg   0.395 lbs                                                           |
| <b>Certifications and Compliance</b> |                                                                                |
| ISO 9001:2015                        | Designed, manufactured and/or distributed under this quality management system |
| RoHS                                 | Compliant                                                                      |

