

Feeder Cable Clamp, 10 holes, 4x9-11mm+6x4-7mm, Salt Spray 720 hours

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



Classification	
Item Number	6008493
Part number	-
Detail Description	Feeder cable clamp, for 4x9-11mm OD cable and 6x4-7mm OD cable, salt spray 720 hours
General Specifications	
Metal Material	Stainless Steel 304
Metal Color	Natural
Block Material	PP
Block Color	Black
Rubber Material	EPDM
Rubber Color	Black
Mounting	M8 Hardware
Cables Per Hanger	10
Dimensions	
Height	40.0 mm 1.57 in
Width	39.0 mm 1.54 in
Length	220 mm 8.66 in
Threaded Rod Length	150.0 mm 5.91 in
Compatible Cable 1 OD, maximum	14.0 mm 0.55 in
Compatible Cable 1 OD, minimum	9.0 mm 0.354 in
Compatible Cable 2 OD, maximum	7.0 mm 0.276 in
Compatible Cable 2 OD, minimum	4.0 mm 0.157 in
Environmental Specifications	
Operating Temperature	-40°C to +85°C(-40°F to +185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994



Salt Spray	≥720 Hours, base on IEC60028-2-11
Packaging and Weights	
Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.278 kg 0.613 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

